



THE SL 2 SUBCOMPACT VACUUM LIFTING SYSTEM is the ultimate attachment—lightweight and extremely versatile, you will wonder how you ever got through a day's work without it! Featuring all-aluminum construction, the patent pending design runs off the host machine's hydraulic system and can be easily attached in minutes to any skid steer to lift steel plate, saw-cut concrete, granite and marble slabs, landscape pavers and more! In addition, quick-connect hydraulic hoses make switching between attachments fast and easy so you can maximize productivity on the job—with the help of the SL 2 you can cut concrete, remove the sections and pour new concrete all in the same day. Perfect for floor, sidewalk, driveway, road and landscaping projects.

- **Hydraulically driven vacuum pump operates using the auxiliary hydraulics from the host machine (minimum 10 GPM required with maximum 3,000 PSI)**
- **Includes quick-connect hydraulic hoses and integrated 24" x 24" vacuum pad with Tough Seal**
- **Universal mounting plates allow easy attachment to most skid steer models**
- **Factory pre-set flow control valve to ensure optimal performance on any host machine**
- **Designed to lift concrete, marble, granite, metal, steel, iron and landscape pavers**
- **Compatible with all skid steer brands**
- **Also compatible with small excavators, backhoes and cranes using the clevis hook connection**

SPECIFICATIONS

LIFTER	CAPACITY	WEIGHT	DIMENSIONS
SL 2	2,700 lb (1.25 tonne)	98 lb (45 kg) w/o plate	L 28" (711 mm) x H 20.75" (527 mm) x W 28" (711 mm)

PARTS & ACCESSORIES

PT3000-700A Tough Seal™, 10 ft (3 m)
SL2-KIT Filter Kit

PT8300-100A Mounting Assembly for Mini Skid Steer
PT8300-200A Mounting Assembly for Standard Skid Steer

